



Versatility is the keyword for the superbly engineered DBS-30.3. Not only does it support 3D video and a huge array of other A/V formats on a variety of disc types, it also puts streaming content from your local network at your fingertips.

ADVANCED FEATURES

- Supports Blu-ray 3D Playback (When Connected to a 3D-Compatible TV)
- HDMI® Output Supports 3D, 1080p, DeepColor™, x.v.Color™ (JPEG Only), and CEC
- Dolby® TrueHD and Dolby® Digital Plus Decoding
- Supports DTS-HD Master Audio™ Essential
- Upscaling of All Standard-Definition Video Sources to 1080p (1080i, 720p, and 480p)
- Certified with DLNA ver. 1.5 for Streaming Videos, Photos, and Music
- Plays AVCHD*, MP3, WMA and JPEG Formats
- BD-Live Functionality for Interactive Content
- Ethernet Port for BD-Live, DLNA, Firmware Updates, and Media Streaming via Internet or Home Network
- Center Mounted Drive Mechanism for Optimal Weight Balance
- 1080/24p Video Output for Full-HD Movies
- USB Port for Media Content

*Encoded on DVD±R/RW only

OTHER FEATURES

- Plays BD-Video (BD-ROM, BD-R/RE), DVD-Video (DVD-ROM, DVD±R/RW, DVD±R DL), Audio CD, MP3 CD, DTS-CD, and CD-R/RW*
- 2 Digital Audio Outputs (Optical/Coaxial)
- Audio, Component, and Composite Video Outputs
- 19 mm-Pitch Audio Output for High-Grade Cable
- Picture-in-Picture Video and Audio Configuration (BD Only)
- On-Screen Display for Settings and Playback (English/French/Spanish)
- Display Dimmer (Auto/Bright/Dimmer)
- Repeat Playback Modes for BD, DVD, and CD (All/Chapter/Title/Track, and A-B [for CD Only])
- Angle and Resume Playback (for BD and DVD)
- Heavy-Duty Detachable Power Cord
- Aluminum Front Panel
- Firmware Updates via Ethernet and USB
- Remote Control

*Discs should be properly finalized.

CUSTOM INTEGRATION FEATURES

- Bi-Directional Ethernet and RS232 Port for Control
- E-control Capability via Ethernet Port
- IR Input / Output
- HDMI CEC for System Control
- 10 HDCP Keys
- Preset Video Adjustments for Sharpness, Contrast, Brightness, Gamma Correction, Color and Noise Reduction
- Optional Rack Mount Kit (IRK-110-3A)



SPECIFICATIONS

VIDEO SECTION

Signal System:	NTSC
Composite Video Output Impedance:	1.0 V(p-p)/75 Ohms, negative sync, RCA
S-Video Output Impedance:	Y: 0.7 V(p-p)/75 Ohms, negative sync, 4-pin mini, DIN C: Y:0.286 V(p-p)/75 Ohms
Component Video Frequency Response:	5 Hz-50 MHz
Component Video Resolution:	480i/480p, 720p, 1080i, 480i (Blu-Ray)
HDMI Video Resolution:	480p, 720p, 1080i/1080p/1080p24 Auto

AUDIO SECTION



Frequency Range:	BD 4 Hz-96 kHz (192kHz)
DVD linear Sound	4 Hz-44 kHz (96kHz) 4 Hz-22 kHz (48kHz)
Audio CD:	4 Hz-20 kHz (44.1 kHz)
SN Ratio:	100dB
Audio Dynamic Range:	86 dB
THD:	0.005% (1 kHz)
Wow and Flutter:	Below threshold of measurebility
Audio Output:	-15 dBm (Digital/Optical)
Audio Output/Impedance:	0.5 Vp-p/75 Ohms(Digital/Coaxial) 2.0 V (rms) / 320 Ohms

GENERAL

Power Supply:	AC 120 V~, 60 Hz
Power Consumption:	22W
Standby Power Consumption:	0.1W
Dimensions (W x H x D):	17 1/8" x 4 1/8" x 12 3/16" (435 x 104 x 309 mm)
Weight:	8.6 lbs. (3.9 kg)

CARTON

Dimensions (W x H x D):	21 11/16" x 8 9/16" x 16 3/16" (551 x 217 x 411 mm)
Weight:	11.9 lbs. (5.4 kg)



Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Blu-ray Disc, Blu-ray, Blu-ray 3D, BD-Live, BONUSVIEW, and the logos are trademarks of the Blu-ray Disc Association. Dolby and the double-D symbol are trademarks of Dolby Laboratories. DTS, DTS-HD, and the DTS symbol are registered trademarks and the DTS logo is a trademark of DTS, Inc. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. x.v.Color is a trademark of Sony Corporation. AVCHD and the AVCHD logo are trademarks of Panasonic Corporation and Sony Corporation. All other trademarks and registered trademarks are the property of their respective holders.